



<b>SPECIFICATIONS FOR TT-510P CNC MACHINE</b>		
	<b>Unit</b>	<b>TT-510P</b>
<b>3 Axes Travels</b>		
X axis travel	inch	20
Y axis travel	inch	16
Z axis travel	inch	14
Distance From Spindle Nose to Table Surface	inch	7.9 – 21.6
<b>Spindle</b>		
Spindle speed	rpm	Direct Driven 12,000
Spindle motor	hp	5/7.5
Spindle nose	BT	BT30
<b>Table</b>		
Table Dimensions	inch	24 x 16
APC Change Time	sec	5
Pallet Top Surface Configuration	inch	.55 x .12 x 4
Table Load Capacity	lbs	550
<b>Rapid Traverse</b>		
Rapid Travel (X/Y/Z)	in/m	1890
Cutting Feed Rate	in/m	400
<b>ATC</b>		
Tool Change Type		Arm
Tool Capacity	set	20
Max. tool weight	lbs	6.6
Max. tool length	inch	7.9
Max. tool diameter	inch	3
Tool Change Time (T-T)	sec	1.5
Tool Change Time (C-C)	sec	2.5
<b>Others</b>		
Compress Air Supply	psi	85
Machine Size (LxWxH)	inch	62 x 110 x 95
Net Weight	lbs	8,800
Gross Weight	lbs	9,900

Machine dimensions and specifications are subject to change without prior notice